


MIGRATORY CORROSION INHIBITOR™ (MCI®) PRODUCTS FOR CONCRETE



MCI®-2000



PRODUCT DESCRIPTION

MCI®-2000 is a liquid concrete admixture; utilizing Migratory Corrosion Inhibitor technology, it protects steel reinforcing, carbon steel, galvanized steel and other metals embedded in concrete. Corrosion induced by carbonation, chloride and atmospheric attack can be prevented with the use of MCI®s. When incorporated into the concrete mix, MCI®-2000 seeks out and forms a corrosion inhibiting layer on the metals. When used with repair mortars and grouts, MCI®-2000 will migrate through undisturbed concrete providing effective corrosion protection to rebars already in place.

WHERE TO USE

MCI®-2000 is recommended for:

- All reinforced, precast, prestressed, post-tensioned or marine concrete structures.
- Steel-reinforced concrete bridges, highways and streets exposed to corrosive environments (carbonation, deicing salts and atmospheric attack).
- Parking decks, ramps and garages.
- All reinforced marine concrete structures.
- Concrete piers, piles, pillars, pipe and utility poles.
- Restoration and repair of all reinforced concrete commercial and civil engineered structures.

ADVANTAGES

- Offers engineers, owners, contractors, DOTs and government agencies a time proven corrosion inhibiting technology that will extend the life of all reinforced concrete structures.
- Protects against the harmful effects of corrosion even in the densest concrete.
- Does not affect the physical properties of the concrete mix (air entrainment, set time, strength or slump).
- Required dosage is not affected by chloride concentration.
- Does not contain any calcium nitrite.
- Organic, safe and environmentally friendly.
- Thoroughly lab and field tested worldwide.
- Concentrated for cost effectiveness on all projects.
- Protects both anodic and cathodic areas.
- Will migrate to adjacent areas to protect surrounding metals.

DOSAGE

Add to concrete mix or repair mortars and grouts at 1 pint per cubic yard (0.6 liter/cubic meter).

APPLICATION

MCI®-2000 can be added to concrete at the ready-mix plant, directly to the ready-mix truck drum, to portable mixers or directly into repair mortars. Mix concrete and mortars thoroughly.

TYPICAL-PROPERTIES

Appearance	Clear yellow-green to green liquid
Density	7.4 - 7.7 lb/gal (0.89 - 0.93 kg/l)
pH	10 - 11 (neat)
Flash Point	103°F T.C.C (39°C) 115°F T.O.C. (46°C)
Shelf Life	24 months in a sealed drum

PACKAGING AND STORAGE

Product is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes and bulk. Store containers below 100°F (38°C) and away from heat or open flame.

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.CortecVCI.com>

printed on recycled paper  10% post consumer

Revised 12/20/06. Cortec Corporation 2002-2006. All rights reserved. Supersedes: 4/08/02
Cortec®, MCI®, and VpCI™ are trademarks of Cortec Corporation