

MCI®-2060

PRODUCT DESCRIPTION

MCI-2060 is a cleaner and degreaser that contains Migratory Corrosion Inhibitors® (MCIs). It effectively cleans caked on grease, dirt, oil, and mud on concrete driveways, garage floors, walkways and curbs; making them look like new. MCI®-2060 contains inhibitors which migrate into concrete, providing protection to rebars and all metals in contact with concrete.

FEATURES

- Good for various oils and greases
- Will not damage sealed or painted surfaces
- Non-flammable
- Remains active even if left to dry
- Non-toxic and biodegradable
- May be used at room temperature to reduce energy consumption
- Viscous liquid will cling to ceilings and vertical surfaces in a ready-to-use formulation
- Replaces caustic-based and strong acid-based concrete cleaners
- No special protective equipment needed for application
- Provides corrosion protection for rebars and all metals which are in contact with concrete
- Adjacent areas do not need special protection during application
- Removes cosmoline, transit coatings, and sludge

TYPICAL APPLICATIONS

- Removal of oils, greases, dirt from all concrete and ceramic surfaces
- Cleaning/degreasing of sealed or painted concrete surfaces
- Can be used to neutralize one of Cortec's VpCI® rust removers (VpCI 422, VpCI 423, VpCI 426, etc.)

APPLICATION

For cleaning:

1. Brush, roll, or spray MCI-2060 onto a concrete surface.
2. Use a deck brush to agitate the surface.
3. Allow MCI-2060 time to clean. Depending on how soiled the surface is, it may take several minutes to one hour.
4. Rinse the loosened grime from the concrete surface using water. If possible, use a pressure washer. Floors may also be flooded with water and the debris brushed away or wet-vacuumed up.

TYPICAL PROPERTIES

| | |
|----------------------|---------------------------------|
| Appearance | Clear light yellow liquid |
| Density | 8.6-8.7 lb/gal (1.03-1.04 kg/l) |
| pH | 10.9-11.4 (Neat) |
| Non-volatile Content | 18-25% |
| Usage | 1% up to concentrate |

LIMITATIONS

The MCI it contains is not designed for long term corrosion protection or to penetrate/migrate distances into concrete. MCI-2060 can only protect reinforcing metal when applied to bare concrete or directly onto the metal.

PACKAGING AND STORAGE

MCI-2060 is available in 5 gallon (19 liter) plastic pails, 55 gallon (208 liter) metal drums, liquid totes, and bulk. Store between 32°F (0°C) and 120°F (49°C).

Migratory Corrosion Inhibitors® (MCI) is a registered trademark of Cortec Corporation.



FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.


BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer
Revised 6/8/11. Cortec Corporation 2000-2011. Supersedes: 6/10/08.
©2011. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited.
ISO accreditation applies to Cortec's processes only.