

VpCI[®]-427



PRODUCT DESCRIPTION

VpCI-427 is a heavy-duty concentrate designed to remove oxide scale from parts and equipment fabricated from aluminum alloys, and as a preparation of aluminum surfaces for further processing such as anodizing, electroplating, or coating. In the past, mineral acids and caustic soda proved to be of limited effectiveness when used as cleaners for aluminum substrates. Another shortcoming of using aluminum cleaners currently available on the market is the scale formation upon heating and significant environmental risks involved with those products.

VpCI-427 is designed to overcome the disadvantages of conventional products. It dissolves aluminum oxide film from the surface and subsequently prevents its depositing an oxide scale. VpCI-427 is environmentally acceptable.

TYPICAL USES

- Aluminum structural elements, automotive components, and castings
- Aircraft parts and components
- Preparation of aluminum surfaces before anodizing, painting, and electroplating

FEATURES

- Replaces mineral acids and caustic soda
- Resists scale formation
- Environmentally acceptable

APPLICATION

Light cleaning: 1 part VpCI-427 to 15 parts water
 Normal cleaning: 1 part VpCI-427 to 8 parts water
 Heavy-duty cleaning: 1 part VpCI-427 to 5 parts water

Time of exposure in the solution will depend on the needs for corrosion removal. VpCI-427 may be rinsed off with water or Cortec[®] VpCI-410 series to provide extra protection. For a bright finish, Cortec[®] VpCI-426 is recommended.

PHYSICAL PROPERTIES

Appearance	Dark brown liquid
Non-volatile Content	40-45%
Weight per Gallon	11.4-11.5 lb/gal. (1.37-1.38 kg/l)

Toxicological Testing Results

Test Species	NOEC/LOEC ppm	48-hr LC50* ppm
D. pules	100/1000	316
P. promelas	100/1000	304
M. beryllina	1000/5000	1510
M. bahia	100/1000	304

* LC-50/EC-50 - 50% of Lethal concentration/50% of Effective Concentration respectively

PACKAGING AND STORAGE

VpCI-427 is available in 5 gallon (19 liter), 55 gallon (208 liter) drums, totes, and bulk.

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

NOT FOR INTERNAL CONSUMPTION

CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.


BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer
Revised 7/10/12. Cortec Corporation 1998-2012. Supersedes: 7/10/03. ©2012. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only.